



ENEOS CITY Performance GEAR Oil

High Performance 4T SCOOTER Gear Oil

This high performance Scooter Gear Oil is specially formulated for scooter gearboxes with dry clutch and using a separate transmission oil from engine oil (gearbox case is separated from engine crankcase). Designed for best lubricating performance during extreme conditions, cold start, short and long city-rides, high temperatures and engine idling at traffic lights and in traffic jams. Engineered to provide smooth gear shifting and increase gear life.

PERFORMANCE STANDARDS

API SJ

Designed to provide low friction coefficient meeting JASO MB standard.
Engineered for OEM performance in Japanese Motorbikes.

APPLICABLE MOTORBIKES

Designed specifically for transmissions in modern 4 Stroke scooters, maxi-scooters, 3-wheelers and motorcycles with "dry type" clutch system, with or without catalytic converters, requiring JASO MB, SAE 10W40 gear oil specification..

Strictly not to be used in wet clutch motorcycle engines

CONTAINERS

1L, 4L, 60L, 200L.

TYPICAL PROPERTIES

SAE viscosity grade	10W-40
Density (15°C), g/cm ³	0.87
Flash point (COC), °C	225
Kinematic viscosity	
(40°C), mm ² /s	96.70
(100°C), mm ² /s	14.35
Viscosity index	150
Pour point, °C	-30.0
TBN (HClO ₄), mg KOH/g	9.8
Appearance	Clear

Note: The typical properties may be changed without notice. (December 2015)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR, NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.

